

16FE+2GE+1GF Uplink HiPoE 300M 200W Long Range PoE Switch

Model: PS11602FE



The PS11602FE Is An Unmanaged PoE Switch With 16 PoE Ports, 2 Gigabit RJ45 Uplinks, And 1 Gigabit SFP Port. Ports 1-12 Supply Up To 30W, Ports 13-16 Up To 60W, Max 200W Total. It Auto-Detects PoE Devices, Powering APs, Webcams, VoIP, And Intercoms, Ideal For Hotels, Campuses, Factories, And SMEs.

- 16FE+2GE+1GF Uplink HiPoE 300M Long Range PoE Switch
- Supports smart watchdog function to monitor compliant PD
- Port 13-16 supports Hi-PoE power up to 60W fit IEEE 802.3bt compliant PDs
- Port 1-12 supports PoE 30W fit IEEE 802.3af/at compliant PDs
- Support VLAN
- Internal power adapter supply 200W (included)
- Support port priority

Interfaces

Model	PS11602FE
Fixed Port	16*10/100Base-T/TX PoE ports (Data/Power) 2*10/100/1000Base-T/TX RJ45 ports (Data) 1*100/1000Base-X uplink SFP fiber slot (Data)
Network Protocol	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000base-X; IEEE802.3x.
Ethernet Port Feature	10/100/1000Base-T(X) automatic detection, full/half Duplex MDI/MDI-X adaptive
Fiber Port Feature	Gigabit SFP Port (Fiber module is not included, need to order separately, module options include single/multi-mode, single/dual fiber, LC)
Forwarding Mode	Store and Forward

PoE

PoE Port	Port 1-16 support PoE @ IEEE802.3af/at
Feature	With the Dial code switch, support port priority by default. E: AI Extend 300meters transmission and auto speed change of single port (limit 10Mbps), other ports maintain 100M/1000M within 100 meters; V: Turn on, 1-16 Port support each port Isolation & VLAN; W: Turn on, 1-16 Port support AI-PoE Network self-healing mode (PoE Watchdog function), Automatic solve the camera problem &reduce after-sale.
Fan	Non-Fan, silent working status can satisfy more users with different requirement.
PoE Standard	IEEE802.3af/at

Switch Property

Switching Capacity	9.2Gbps (non-blocking)
Forwarding Rate	6.84Mpps
MAC address table	8K
Buffer Memory	4M
Twisted Pair Transmission	10BASE-T: Cat5 UTP (≤300 meter) 100BASE-TX: Cat5 or later UTP (≤100 meter) 1000BASE-TX: Cat5 or later UTP (≤100 meter)
Power Supply Pin	Default 1/2(+), 3/6(-)
MAX Power Per Port	Port 1-14 30W, port 15-16 60W
Total PWR / Input Voltage	200W
Power Consumption	Standby:<5W Full load:<200W

Physical Characteristics

LED Indicator	Power indicator: PWR (Green); Network indicator: 1-16(Link/Act)/ (Green),17-19(Link/Act)/ (Green)
Power Supply	Build-in power adaptor AC100~240V 50-60Hz,200W
Operation TEMP / Humidity	-20~+55°C:5%~90% RH non condensing
Storage TEMP / Humidity	-40~+75°C;5%~95% RH non condensing
Dimension	310*205*44mm

Certification

Certification	CE, FCC, RoHS
---------------	---------------

Package Contents

Switch	1 pcs
Power cord	1 pcs
Hanging Ears	1 pcs
Quick installation guide	1 pcs



Maxsol Technologies Limited

Website

www.maxsol-tech.com

Phone

+86 19849790018

Email

sales@maxsol-tech.com

Address

Building 2, No. 3, Shangcun Industrial Zone, Tiantou Community, Shijing Subdistrict,
Pingshan District, Shenzhen, China

